

ET-1095 Industrial Endoscope



TECHNICAL SPECIFICATIONS

Model		ET-1095
Host	Dimension	350*155*59mm
	Display	5 inch industrial LCD screen
	Output port	HDMI video output, Micro USB, TF card slot
	Storage	32G
	Power	Special rechargeable lithium battery pack, online charging, battery life ≥4 hours
	IP grade	IP54
	Working temperature	-10°C ~50°C
	Storage temperature	-20°C ~60°C
System	Relative humidity	Max 95%, No condensation
	Operation System	Multifunctional operating system
	Operation method	Button navigation, dual camera and video buttons
	Support Function	With freeze, zoom, photo, flip, video playback, analog ruler functions
	File Format	Image:JPEG (JPG), Video:AVI
Packing Case	Support Language	Chinese (Simplified and Traditional), French, English, German, Spanish, Italian, Japanese
	Weight	3.9kg
	L*W*H	47.9*38.7*15.5cm

CAMERA AND PROBE

There are several length and diameters for ET-1095 series for you to choose according to requirement.

Model		ET-1180
Lens	Direction	Direct view
	View angle	120°
	(DOF)	3~70mm
	Pixels	160000
	Illumination system	Rear high-power LED fibre optic transmission
Probe	Lenght (L)	Direct view/Side view: 4.5±0.5mm Double view: 9±0.5mm
	Diameter (D)	0.95mm
	Articulation	No articulation
	Working temperature	-20°C~70°C
Inserting Tube	Length	0.5m
	Materials	Bourdon Tube